

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application:

1-8. (Cancelled).

9. (Previously Presented) A drive mechanism for a drug delivery device comprising:

- an epicyclic gearbox;
- a housing including a helical thread;
- a piston rod including a non-circular cross-section and an external helical thread;
- a dose dial sleeve configured to engage with the helical thread of the housing and configured to rotate relative to the housing; and
- a drive sleeve configured to be disposed between the housing and the piston rod, the drive sleeve being configured to engage with the external helical thread of the piston rod.

10. (Previously Presented) The drive mechanism of claim 9, wherein the dose dial sleeve is configured to be releasibly connected to the drive sleeve via the epicyclic gearbox.

11. (Cancelled).

12. (Previously Presented) An assembly for use in a drug delivery device, comprising:

- a drive mechanism including an epicyclic gearbox;
- a housing including a helical thread;
- a piston rod including a non-circular cross-section and an external helical thread;
- a dose dial sleeve configured to engage with the helical thread of the housing and configured to rotate relative to the housing; and
- a drive sleeve configured to be disposed between the housing and the piston rod, the drive sleeve being configured to engage with the external helical thread of the piston rod.

13. (Previously Presented) The assembly of claim 12, wherein the dose dial sleeve is configured to be releasibly connected to the drive sleeve via the epicyclic gearbox.

14. (Currently Amended) A drug injection device, comprising a housing, a first portion of the housing being configured to receive a medicinal product to be injected, and a second portion of the housing containing a drive mechanism including an epicyclic gearbox.

15. (Previously Presented) A drug delivery device, comprising:

- a drive mechanism including an epicyclic gearbox;
- a housing including a helical thread;

a piston rod including a non-circular cross-section and an external helical thread;
a dose dial sleeve configured to engage with the helical thread of the housing
and configured to rotate relative to the housing; and
a drive sleeve configured to be disposed between the housing and the piston rod,
the drive sleeve being configured to engage with the external helical thread of the piston
rod.

16. (Previously Presented) The drug delivery device of claim 15, wherein the
dose dial sleeve is configured to be releasibly connected to the drive sleeve via the
epicyclic gearbox.

17. (Currently Amended) A method of assembling a drug injection device,
comprising:
providing a housing, the housing including a first portion and a second portion,
the first portion being configured to receive a cartridge containing a medicinal product to
be injected; and
providing a drive mechanism including an epicyclic gearbox in the second portion
of the housing.

18. (Previously Presented) A method of assembling a drug delivery device,
comprising:
providing a drive mechanism including an epicyclic gearbox;
providing a housing including a helical thread;

providing a piston rod including a non-circular cross-section and an external helical thread;

providing a dose dial sleeve configured to rotate relative to the housing;

providing a drive sleeve;

engaging the dose dial sleeve with the helical thread of the housing;

placing the drive sleeve between the housing and the piston rod; and

engaging the drive sleeve with the external helical thread of the piston rod.

19. (Previously Presented) The method of claim 18, further comprising:

releasibly connecting the dose dial sleeve to the drive sleeve via the epicyclic gearbox.

20. (Currently Amended) A method of assembling a drug injection device, comprising:

providing a housing having a first portion and a second portion, the first portion of the housing being configured to receive a cartridge containing a medicinal product to be dispensed; and

providing an assembly including a drive mechanism including an epicyclic gearbox in the second portion of the housing.

21. (Previously Presented) A method of assembling a drug delivery device, comprising:

providing an assembly including a drive mechanism including an epicyclic gearbox;

providing a housing including a helical thread;

providing a piston rod including a non-circular cross-section and an external helical thread;

providing a dose dial sleeve configured to rotate relative to the housing;

providing a drive sleeve;

engaging the dose dial sleeve with the helical thread of the housing;

placing the drive sleeve between the housing and the piston rod; and

engaging the drive sleeve with the external helical thread of the piston rod.

22. (Previously Presented) The method of claim 21, further comprising:

releasibly connecting the dose dial sleeve to the drive sleeve via the epicyclic gearbox.

23. (Previously Presented) A method of dispensing a medicinal product, comprising:

providing a drug delivery device including a drive mechanism including an epicyclic gearbox;

dispensing the medicinal product via the drug delivery device;

wherein the medicinal product includes an active ingredient selected from the group consisting of insulin, growth hormone, low molecular weight heparin, analogues of insulin, analogues of growth hormones, analogues of low molecular weight heparin,

derivatives of insulin, derivatives of growth hormones, and derivatives of low molecular weight heparin.

24. (Previously Presented) The method of claim 23, wherein the drug delivery device further comprises:

- a housing including a helical thread;
- a piston rod including a non-circular cross-section and an external helical thread;
- a dose dial sleeve configured to engage with the helical thread of the housing and configured to rotate relative to the housing; and
- a drive sleeve configured to be disposed between the housing and the piston rod, the drive sleeve being configured to engage with the external helical thread of the piston rod.

25. (Previously Presented) The method of claim 24, wherein the dose dial sleeve is configured to be releasibly connected to the drive sleeve via the epicyclic gearbox.

26. (New) The device of claim 14, wherein the first portion of the housing is configured to receive a cartridge containing a medicinal product to be injected.

27. (New) The device of claim 26, further comprising an element configured to dispense a medicinal product and disposed within the housing.

28. (New) The device of claim 27, wherein the element configured to dispense a medicinal product is a piston.

29. (New) The device of claim 28, wherein the epicyclic gearbox is configured to transmit a force to the piston to dispense a medicinal product from the drug injection device.